

MODEL AQE2000

Portable Cartridge System



The new Portable Cartridge System from Air Quality Engineering Inc. is a complete self-contained media air cleaner for use in source capture applications in industry. The Model AQE2000 captures airborne contaminants such as welding smoke, grinding dust, plastic dust and other fine particles.



**AIR QUALITY
ENGINEERING**

Manufacturer and Worldwide Distributor of Air Cleaning Systems for Over 30 Years

AQE 2000 FEATURES & SPECIFICATIONS

Principles of Operation:

Airborne contaminants enter the AQE2000 through the hood/arm assembly at a rate of 1100 cubic feet of air per minute (cfm). Heavy particles are propelled downward through the venturi and into the clean out trays. Small submicron particles are then trapped within the pleats of the two 99.8% efficient cartridge filters. The cleaned air is then gently diffused out the bottom of the unit. When the filter gage indicates that the cartridge filters are dirty, they are easily cleaned by connecting a shop air hose (80-120 psi) to the unit and activating the reverse pulse system.

STANDARD FEATURES :



- Air volume - 1100 cfm
- Reverse pulse cleaning system
- Externally supported 11' arm. Full 360° rotation.
- 1.5 horse power motor
- 382 square feet of filter media
- 99.8% efficient at .5 micron
- Large 8" diameter front wheels
- Quiet operation
- Three-year limited warranty

OPTIONAL FEATURES :

- Halogen light
- 2nd stage HEPA filter

SPECIFICATIONS :

DIMENSIONS:	46"H x 28.5"W x 37"D
WEIGHT:	400 lbs actual, 450 lbs shipping
ARM ASSEMBLY	11' long x 8" diameter. Externally supported arm with full 360° arm rotation. Arm assembly incorporates a gas spring which provides easy up and down movement.
HOOD:	18 Ga. aluminum hood with handle. Hood moves easily vertically and horizontally.
AIRFLOW VOLUME:	1100 cfm
MOTOR:	1.5 HP thermally protected
BLOWER:	Direct drive, backward incline
CABINET CONSTRUCTION:	16 Ga. welded CRS steel
CONTROLS:	All models include control circuitry and thermal protection.
POWER:	120V/60 hz/14 amp running or 208-240V/60 hz/8 amp running. Ten-foot power cord with molded plug standard on single phase models, 3 phase models available at no extra charge.
CASTERS:	Two large 8" diameter semi-pneumatic (front) wheels and two heavy duty swivel casters (back)
FINISH:	Durable powder coat paint
FILTRATION:	Two high efficiency cartridge filters: 12 3/4" (diameter x 22" 382 sq. ft. total, 99.8% efficient at .5 micron
FILTER ACCESS:	Hinged side door
FILTER CLEANING:	Self-Cleaning Reverse Pulse Jet System which utilizes a one inch diaphragm valve. Requires 80 -120 psi of shop supplied compressed air. 1/4" NPT female fitting is provided to accept field installed quick connect.
FILTER GAGE:	Dirty filter gage indicates pressure up to 10" H 2O
NOISE LEVEL:	73 dBA at 6"
WARRANTY:	Limited three year warranty



**AIR QUALITY
ENGINEERING**

7140 Northland Drive North, Brooklyn Park, MN 55428-1520 USA

FAX: (763) 531-9900 EMAIL: info@air-quality-eng.com WEB SITE: www.air-quality-eng.com

TOLL FREE: 1-800-328-0787 PHONE: (763) 531-9823